

WASTE AWAY®

IMPROVING THE ENVIRONMENT

RECOMMENDED APPLICATIONS

WASTE LAGOONS



- **Initial treatment:** Apply 2 gallons per surface acre of lagoon or 16 ounces treats 3,000 cubic feet (approximately 22,500 gallons).
- **Maintenance treatment:** Treat daily with one gallon per surface acre.
- As more waste is added more Waste Away®, will need to be added.
- 1-gallon minimum treatment for small lagoons.
- Treatment may vary due to feeding program and size of lagoons.
- Mix Waste Away® with water and spray over area to be treated. If possible, distribute over the entire surface; do not pour on just one area.
- Use a spray applicator to achieve even distribution of Waste Away® in the lagoon.
- Agitation is very helpful.

COMPOST STARTER



- Apply 8 to 16 ounces of Waste Away® per ton (2 cubic yards) of compost material.
- Mix Waste Away® with water to achieve moisture range of 45-60%. Apply early in the composting process.
- Use normal watering practices to maintain sufficient moisture of the compost.
- **For field application:** Apply directly to crop residue at a rate of 1 gallon per 100 gallons of water for up to 10 acres. Apply as soon after harvest as possible.

MANURE COLLECTING TANKS

- **Initial treatment:** Use one (1) gallon for each 2,000 cubic feet (15,000-16,000-gallon capacity) once every four (4) days for the first month.
- **Maintenance treatment:** Add one-half gallon per 2,000 cubic feet, weekly, or whenever manure is added.

MAXIMUM EFFICIENCY

Automated Application Systems

For information, please call
CXI - 972.471.7775



1100 E. Sandy Lake Rd.
Coppell, TX 75019
Ph: 972.471.7775
www.cxinternational.com